

# EMT-60-HL

## Magnetic Dimmable

Outdoor Black Powder Coated Steel Enclosure

Multi Tap: **12-15VAC**

Total Wattage: **60W max**


Input Voltage: **120V 60Hz**



www.emcod.com



Conforms to UL STD. 1838  
Certified to CSA  
STD. C22.2 No 250.0, 250.7



### Transformer

Dimmable with any LV magnetic dimmer as long as you cover dimmer's min load.

Temperature class B(130°C)

Input leads: Line cord

Output leads: Terminal Block

Magnetic manually reset secondary breaker 7A

Timer and photocell build in options

### Housing

The actual transformer 60W is encapsulated in the enclosure


The enclosure is Black Powder Coated Steel, NEMA 3R rated

Wiring compartment has 4 knockouts sizes for 3/8 inch screw cable connectors

Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded

Dimensions (inch): H = 11.19, W = 5.65, D = 5.54

Weight (LBs): 11.5



### Electrical Parameters

Input Voltage: **120V 60Hz**

Max. input current at full load: **0.63A**

Output voltage without load: **12.4/ 13.4/ 14.1/ 15.4VAC**

Output voltage fully loaded: **11.4/ 12.4/ 13.3/ 14.3VAC**

Max. Total Wattage: **60W**

Max. Output Current: **5/ 4.6/ 4.3/ 4A**

Efficiency: **90%**

Load regulation: **9%**

Mailing Address: 15545 Cabrito Rd. Van Nuys, CA 91406 Tech support: Arik Nirenberg phone: 818-904-3309 cellphone: 818-269-4091  
Fax: 818 904 3327 info@emcod.com techsupport@emcod.com