

SS120W

Magnetic Non Dimmable

Outdoor Stainless Steel Enclosure


Multi Tap: **12VAC and 15VAC**

Total Wattage: **120W max**

Input Voltage: **120V 60Hz**



Conforms to UL STD. 1838
Certified to CSA
STD. C22.2 No 250.0, 250.7
model SS120W
[Link to certification](#)



Transformer

Non Dimmable

Temperature class B(130°C)

Input leads: Line cord

Output leads: Terminal Block

Thermal manually reset secondary breaker 20A

Timer and photocell build in options

Housing

The actual transformer 120W is encapsulated in the enclosure

The enclosure is Stainless Steel, NEMA 3R rated

Enclosure Temperature does not exceed 70°C at 45°C ambient and fully loaded

Dimensions (inch): H = 8.47, W = 5.31, D = 3.65

Weight (LBs): 7.12

Electrical Parameters

Input Voltage: **120V 60Hz**

Max. input current at full load: **1A**


Output voltage without load: **12/ 15VAC**

Output voltage fully loaded: **11.5/ 14.5VAC**

Max. Total Wattage: **120W**

Max. Output Current: **10/ 8A**

Efficiency: **90%**



Mailing Address: 646 Flinn Ave. Unit B, Moorpark, CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309
Fax: 818 904 3327 info@emcod.com techsupport@emcod.com