

EMT1200SS-22E

Magnetic

Outdoor Stainless Steel Enclosure


Multi Tap: **12-22VAC**

Total Wattage: **1200W max**

Input Voltage: **120V 60Hz**



Conforms to UL STD. 1838
Certified to CSA
STD. C22.2 No 250.0
model -



Transformer

Temperature class B(130°C)

Two section bobbin completely separated primary and secondary windings

Input leads: Line cord

Output leads: Terminal Block

Leads max. operational temperature is 105°C

Magnetic manually reset secondary breaker 25A per circuit

Timer and photocell build in options

Housing

The actual transformer 1200W is encapsulated in the enclosure

The enclosure is Stainless Steel, NEMA 3R rated

Wiring compartment has 6 knockouts sizes for 3/8 inch screw cable connectors

Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded

Dimensions (inch): H = 18.62, W = 7.8, D = 6.87

Weight (LBs): 47

Electrical Parameters

Input Voltage: **120V 60Hz**

Max. input current at full load: **10A**


Output voltage without load: **12.5/ 14.5/ 15.5/ 16.5/ 18.5/ 20.5/ 22.5VAC**

Output voltage fully loaded: **11.5/ 13.5/ 14.5/ 15.5/ 17.5/ 19.5/ 21.5VAC**

Max. Total Wattage: **1200W** Max. per circuit: **300W**

Max. Output Current: **25/ 21/ 20/ 19/ 17/ 15/ 13.6A** per circuit.

Efficiency: **95%**



Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309

Fax: 818 904 3327 info@emcod.com techsupport@emcod.com