

# EMT-300-H

## Magnetic Dimmable

Outdoor Black Powder Coated Steel Enclosure

Multi Tap: **12-15VAC**

Total Wattage: **300W max**


Input Voltage: **120V 60Hz**



www.emcod.com



Conforms to UL STD. 1838  
Certified to CSA  
STD. C22.2 No 250.0, 250.7



### Transformer

Dimmable with any LV magnetic dimmer as long as you cover dimmer's min load.

Temperature class B(130°C)

Input leads: Line cord

Output leads: Terminal Block

Magnetic manually reset secondary breaker 25A

Timer and photocell build in options

### Housing

The actual transformer 300W is encapsulated in the enclosure

The enclosure is Black Powder Coated Steel, NEMA 3R rated

Wiring compartment has 4 knockouts sizes for 3/8 inch screw cable connectors

Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded

Dimensions (inch): H = 17.05, W = 5.33, D = 5.5

Weight (LBs): 17.6

### Electrical Parameters

Input Voltage: **120V 60Hz**

Max. input current at full load: **2.5A**


Output voltage without load: **12/ 13/ 14/ 15VAC**

Output voltage fully loaded: **11.4/ 12.4/ 13.4/ 14.4VAC**

Max. Total Wattage: **300W**

Max. Output Current: **25/ 23/ 21/ 20A**

Efficiency: **93%**



Mailing Address: 6925 Eton Ave. Canoga Park, CA 91303 Tech support: Arik Nirenberg phone: 818-904-3309 cellphone: 818-269-4091

Fax: 818 904 3327 info@emcod.com techsupport@emcod.com