# ЕМТ-900-Н

#### Magnetic

Outdoor Stainless Steel Enclosure Multi Tap: **12-15VAC** Total Wattage: **900W max** Input Voltage: **120V 60Hz** 







Conforms to UL STD. 1838 Certified to CSA STD. C22.2 № 250.0, 250.7

### Transformer

Temperature class B(130°C) Input leads: Line cord Output leads: Terminal Block Magnetic manually reset secondary breaker 25A per circuit Timer and photocell build in options

### Housing

The actual transformer 900W is encapsulated in the enclosure The enclosure is Stainless Steel, NEMA 3R rated Wiring compartment has 6 knockouts sizes for 3/8 inch screw cable connectors Enclosure Temperature does not exceed 75°C at 45°C ambient and fu

Enclosure Temperature does not exceed 75°C at 45°C ambient and fully loaded

Dimensions (inch): H = 18.93, W = 6.58, D = 5.75Weight (LBs): 3.5

# **Electrical Parameters**

Input Voltage:	120V 60Hz	
Max. input current at full load	: <b>7.5A</b>	
Output voltage without load:	12/ 13.4/ 14.2/ 15.3VAC	
Output voltage fully loaded:	11.4/ 12.6/ 13.6/ 14.6VAC	
Max. Total Wattage:	900W	Max. per circuit: 300W
Max. Output Current:	25/ 23/ 21/ 20A per circuit.	
Efficiency:	94%	
Load regulation:	0.04%	

Mailing Address: 646 Flinn Ave. Unit B, Moorpark , CA 93021 Tech support: Arik Nirenberg phone: 818-904-3309 Fax: 818 904 3327 info@emcod.com techsupport@emcod.com



